

Technical Information

# **ACRYLITE® LED**

## LED optimized for backlighting (truLED)

#### **Product**

ACRYLITE® LED optimized (truLED) acrylic sheet was specifically developed for backlighting with LEDs and provides maximum transmission and optimum light diffusion. These unique properties deliver a brilliant appearance and eliminate undesired hot spots or fluctuations in luminance, even in ultra slim illuminated signs.

The light transmission of ACRYLITE® LED (truLED) sheet is adjusted to the same wavelength ranges as the respective LEDs. This combination of properties makes it possible to employ modern LED technology with maximum brightness.

### **Properties**

In addition to the high quality and proven performance of ACRYLITE®, such as

- extremely high weather resistance
- · ease of fabrication
- 100% recyclability

ACRYLITE® LED (truLED) offers the following characteristics:

- no LED hot spots due to optimum light diffusion
- high luminous efficiency, and therefore cost savings, through improved diffusion

### **Applications**

These properties make ACRYLITE® LED (truLED) especially suitable for:

 Channel letters, light boxes, backlighting in exhibition booths and store fixtures

#### **Product Specifications**

Color	Standard Size		Transmission TD65
		Thickness	
White			
WH72 GT	80x120	.118"	31%
White			
WH14 GT	80x120	.118"	55%

This product belongs to the ACRYLITE® LED product family and was specially developed for the illuminated sign industry. You can find other interesting products developed for LED applications in the "ACRYLITE® Lighting Product Family Overview" (Ref. No. 3802)



Evonik Cyro LLC | ACRYLITE® LED | 3707A-0213-Cyro Page 2/2

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether expressed or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technical progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products should be used.

Evonik Industries is a worldwide manufacturer of PMMA products sold under the ACRYLITE® trademark in the Americas and under the PLEXIGLAS® trademark in the European, Asian, African, and Australian continents. ©Evonik Cyro LLC. All rights reserved.

Printed in the USA.

Evonik Cyro LLC 299 Jefferson Road, Parsippany, NJ 07054 US Phone +1800 631 5384 www.acrylite.net www.acrylite-shop.com

