

## Adhesive Recommendation Guide

Adhesive	8345	1150	1123	1126	8346	1905 HPA	1191 UHA
<b>Type</b>	Rubber	Acrylic	Acrylic	Acrylic	Acrylic	Acrylic	Rubber
<b>Thickness (inches)</b>	.005"	.002"	.003"	.005"	.005"	.005"	.011"
<b>Substrate</b>							
ABS Plastics	●	●	●	●	●	●	●
Aluminum	●	●	●	●	●	●	●
Carpet							●
Cloth	●	●	●	●	●	●	●
EPDM			●	●	●		
Fiberglass	●	●	●	●	●	●	●
Foam - Polyester Urethane	●	●	●	●	●	●	
Foam - Polyether Urethane		●	●	●	●	●	
Foam - Polyethylene	●		●	●	●		
Glass/Ceramic	●	●	●	●	●	●	●
Metal - Painted	●	●	●	●	●	●	●
Metal - Powder Coated			●	●	●		●
Neoprene		●	●	●	●	●	
Silicone Foam							
Polycarbonate	●	●	●	●	●	●	●
Polyethylene	●		●	●	●		●
Polypropylene	●		●	●	●		●
PVC - Mildly Plasticized		●	●	●	●	●	●
Rubber - Extruded		●	●	●	●	●	
Stainless Steel	●	●	●	●	●	●	●
<b>Environment</b>							
Temperature - Continuous °F	175°	225°	200°	200°	200°	400°	225°
Temperature - Intermittent °F	200°	275°	250°	250°	250°	450°	275°
UV Stable		●	●	●	●	●	
Solvent Resistant		●	●	●	●	●	
Moisture Resistant		●	●	●	●	●	