



Polyurethane Tubing Sizes

(sizes are stated in Inches – I.D. = Inside Diameter, O.D. = Outside Diameter)

Polyurethane--Ether 86A and Ester 85A				
Sizes			Approx.	Working PSI@73°F
I.D. Sizes	O.D. Sizes	Wall Thickness	LBS./C'	Ether / Ester
.062	.125	.031	.5	80/105
.125	.187	.031	.8	55/70
.125	.250	.062	1.9	80/110
.187	.250	.031	1.1	40/55
.187	.312	.062	2.6	65/85
.250	.312	.031	1.4	30/50
.250	.375	.062	3.2	55/75
.250	.437	.093	5.3	70/95
.250	.500	.125	7.7	85/110
.312	.437	.062	3.9	50/65
.312	.562	.125	9.0	75/100
.375	.500	.062	4.5	40/55
.375	.562	.093	7.2	55/75
.375	.625	.125	10.3	70/90
.437	.625	.093	8.2	50/65
.500	.625	.062	5.8	30/40
.500	.750	.125	12.9	55/75
.625	.812	.093	11.1	35/52
.625	.875	.125	15.4	45/60
.750	1.00	.125	18.0	40/55
.875	1.125	.125	20.6	35/45
1.00	1.250	.125	23.2	30/40

For technical details or pricing on any of these grades and sizes, contact Professional Plastics

PROFESSIONAL PLASTICS, INC.

www.professionalplastics.com

sales@proplas.com

USA (888) 995-7767 – Singapore +65 6266-6193 – 台灣 Taiwan +886 (3) 5357850