



PTFE Convuluted Tubing Sizes

Standard Flex Convuluted								Weight (LBS) Per CFT Maximum	Min. Bend Radius
Part Number	Military Spec.	Identifier	Max I.D.	Min I.D.	Max O.D.	Max. Wall Thick	Conv/Inch +/-1"		
ZCT TS-012	AMS-T-81914/1	**01	0.188	0.181	0.32	0.023	8	2.0	0.500
ZCT TS-018	AMS-T-81914/1	**02	0.281	0.273	0.414	0.027	7 1/2	2.9	0.750
ZCT TS-020	AMS-T-81914/1	**03	0.312	0.303	0.45	0.027	7 1/2	3.6	0.875
ZCT TS-024	AMS-T-81914/1	**04	0.375	0.364	0.53	0.029	7	4.2	1.000
ZCT TS-028	AMS-T-81914/1	**05	0.437	0.425	0.59	0.029	7	4.9	1.250
ZCT TS-032	AMS-T-81914/1	**06	0.500	0.485	0.66	0.029	7	5.2	1.500
ZCT TS-040	AMS-T-81914/1	**07	0.625	0.608	0.78	0.035	7	6.9	1.750
ZCT TS-048	AMS-T-81914/1	**08	0.750	0.730	0.975	0.035	6	10.4	1.875
ZCT TS-056	AMS-T-81914/1	**09	0.875	0.850	1.10	0.035	6	11.3	2.250
ZCT TS-064	AMS-T-81914/1	**10	1.000	0.975	1.26	0.035	4 1/2	12.6	2.500
ZCT TS-072	AMS-T-81914/1	**11	1.125	1.105	1.39	0.035	4 1/2	13.8	2.750
ZCT TS-080	AMS-T-81914/1	**12	1.250	1.210	1.539	0.035	4	15.5	3.000
ZCT TS-096	AMS-T-81914/1	**13	1.500	1.440	1.85	0.040	4	21.7	3.750
ZCT TS-079	AMS-T-81914/1	**14	1.750	1.690	2.10	0.045	4	25.3	4.250

The table above details ZEUS and AMS-Spec. numbers and dimensions for our standard PTFE convuluted tubing. Custom sizes and configurations are also available. **PFA does not conform to MIL-T. Please contact us for more information.**

Order Online at

www.professionalplastics.com/CONVULUTEDTEFLONTUBING

Call Professional Plastics at **(888) 995-7767** or
E-Mail sales@proplas.com