



PROFESSIONAL PLASTICS, INC.












Leading Global Supplier of Engineered Plastic Shapes

USA Phone (888) 995-7767 – Asia Phone +65-6266-6193

E-Mail: sales@proplas.com Website: www.professionalplastics.com

WELDING TIPS



	RD free hand/fan welding tip
	HD tacking tip for tack welding to keep parts aligned and in place prior to applying a weld bead
	SSD high speed welding tip, match rod diameter SSD 3 = 1/8" SSD 4 = 5/32", SSD 5 = 3/16" SSD 6 = 1/4"
	SSD/HD combination high speed/tacking tip, match rod diameter SSD/HD 3=1/8", SSD/HD 4=5/32", SSD/HD 5=3/16" SSD/HD 6=1/4"
	SSD/HD-OS combination high speed/tacking tip, mostly preferred for fluoropolymer materials, match rod diameter SSD/HD-OS 3=1/8", SSD/HD-OS 4=5/32"
	SSD-OS high speed welding tip, mostly preferred for fluoropolymer materials, match rod diameter SSD-OS 3=1/8", SSD-OS 4=5/32"
	SSD/WL high speed tip for cap strip rod (steel roller) 18 mm = 5/8" wide
	SSD/WL-G high speed tip with guide for cap strip rod 18 mm = 5/8" wide, with guide
	SSD/Roller high speed tip with roller, match rod diameter 3 = 1/8" or 4 = 5/32"
	Our regular SSD tips are available as angled tips, specify size 1/8" or 5/32", 45° either angled left or right
	SSD/Profile high speed tip for <i>triangular</i> welding rod specify rod size .175 Tri #9 (TIPTR3) 1/8" MW #1 (TIPTR3) 1/8" MWK #5 (TIPTR3) .236 Tri #10 (TIPTR4) 5/32" MW#2 (TIPTR4) 5/32" MWK #6 (TIPTR4) .275 Tri #11 (TIPTR5) 3/16" MW #3 (TIPTRBM) 3/16" MWK #7 (TIPTR5) 1/4" MW #4 (TIPTRUPF) 1/4" MWK #8 (TIPTR1/4)